

FOR EUROPEAN VEHICLES

Type No.	Capacity at 20HR Rate (AH)	DIN	IEC	EN	Max. Overall Dimensions(mm)				Cell Layout	Terminal Type	Bottom Hold Down	Weight with Acid (Kgs)	Delkor Figure No.
		Cranking Performanc at - 18°C(Amps)	Cranking Performanc at - 18°C(Amps)	Cranking Performanc at - 18°C(Amps)	Length	Width	Height	T. Height					
53517/53528	35	170	200	340	209.0	175.0	175.0	175.0	0	D	B3	11.1	13
53518/53529	35	170	200	340	209.0	175.0	175.0	175.0	0	A	B3	11.1	10
53519	35	170	200	340	209.0	175.0	175.0	175.0	1	A	B3	11.1	10
53520	35	150	175	340	197.0	129.0	203.0	227.0	0	B	B0	10.1	1
53521	35	150	175	340	197.0	129.0	203.0	227.0	0	A	B0	10.2	1
53522	35	150	175	340	197.0	129.0	203.0	227.0	1	B	B0	10.1	1
53621/53646	36	175	200	340	209.0	175.0	175.0	175.0	0	A	B4	11.1	12
53624/53653	36	175	200	340	209.0	175.0	175.0	175.0	0	A	B1	11.1	11
53638	36	175	200	340	209.0	175.0	175.0	175.0	1	A	B1	11.1	11
54045	40	220	250	430	209.0	175.0	175.0	175.0	0	A	B4	12.3	12
54312/54317	43	210	240	430	209.0	175.0	175.0	175.0	0	D	B3	12.3	13
54313/54316	43	210	240	430	209.0	175.0	175.0	175.0	0	A	B3	12.3	10
54434/54459	44	210	240	420	209.0	175.0	190.0	190.0	0	A	B3	13.1	10
54437	44	210	240	420	209.0	175.0	190.0	190.0	0	D	B3	13.1	13
54449/54464	44	210	240	420	209.0	175.0	190.0	190.0	1	A	B3	13.1	10
54523	45	190	220	390	238.0	129.0	203.0	227.0	0	A	B0	12.6	1
54524	45	190	220	390	238.0	129.0	203.0	227.0	1	A	B0	12.6	1
54533/54519	45	220	250	430	244.0	175.0	175.0	175.0	0	A	B4	13.4	12
54549	45	220	250	430	244.0	175.0	175.0	175.0	1	A	B1	13.4	11
54551	45	190	220	390	238.0	129.0	203.0	227.0	1	B	B0	12.6	1
54584	45	190	220	390	238.0	129.0	203.0	227.0	0	B	B0	12.6	1
55040/55046	50	300	350	525	244.0	175.0	175.0	175.0	0	A	B3	14.5	10
55041	50	220	250	430	208.0	173.0	202.0	225.0	0	A	B7	13.3	2
55042	50	220	250	430	208.0	173.0	202.0	225.0	1	A	B7	13.3	2
55044	50	265	310	525	244.0	175.0	175.0	175.0	0	A	B4	14.6	20
55066	50	210	240	420	209.0	175.0	190.0	190.0	0	A	B3	13.1	10
55414	54	265	310	520	279.0	175.0	175.0	175.0	0	A	B4	15.5	16

55421/55457	54	300	350	525	244.0	175.0	175.0	175.0	0	A	B3	14.5	10
55422/55458	54	300	350	525	244.0	175.0	175.0	175.0	1	A	B3	14.5	10
55423/55427	54	300	350	525	244.0	175.0	175.0	175.0	0	D	B3	14.5	13
55433	54	300	350	525	244.0	175.0	175.0	175.0	0	A	B4	14.5	12
55530/55559	55	255	295	535	244.0	175.0	190.0	190.0	0	A	B3	15.3	10
55531	55	255	295	535	244.0	175.0	190.0	190.0	0	D	B3	15.3	13
55548/55565	55	255	295	535	244.0	175.0	190.0	190.0	1	A	B3	15.3	10
56030	60	300	350	570	244.0	175.0	190.0	190.0	0	A	B3	15.9	10
56031	60	300	350	570	244.0	175.0	190.0	190.0	1	A	B3	15.9	10
56111	61	300	380	570	244.0	175.0	190.0	190.0	0	A	B4	15.9	12
56219	62	280	320	570	244.0	175.0	190.0	190.0	0	A	B3	15.9	10
56048	60	250	290	480	272.0	173.0	204.0	225.0	0	A	B9	16.9	3
56049	60	250	290	480	272.0	173.0	204.0	225.0	1	A	B9	16.9	3
56068	60	240	270	510	231.0	173.0	204.0	225.0	0	A	B7	16.1	2
56069	60	240	270	510	231.0	173.0	204.0	225.0	1	A	B7	16.1	2
56316/56318	63	300	350	560	279.0	175.0	175.0	175.0	0	A	B4	16.4	16
56320	63	380	440	675	279.0	175.0	175.0	175.0	0	A	B4	17.2	16
56323	63	380	440	675	279.0	175.0	175.0	175.0	0	D	B3	17.3	17
56420	64	380	440	675	279.0	175.0	175.0	175.0	0	A	B4	17.2	16
56530	65	320	360	560	279.0	175.0	175.0	175.0	0	A	B3	16.4	14
56618/56638	66	300	350	510	279.0	175.0	190.0	190.0	0	A	B3	17.3	14
56619	66	300	350	510	279.0	175.0	190.0	190.0	0	D	B3	17.3	17
56637	66	300	350	560	279.0	175.0	175.0	175.0	0	A	B1	16.4	15
57024	70	315	360	550	272.0	173.0	204.0	225.0	1	A	B9	18.7	3
57029	70	315	360	550	272.0	173.0	204.0	225.0	0	A	B9	18.7	3
57219	72	350	400	610	279.0	175.0	190.0	190.0	1	A	B3	18.2	14
57412	74	400	450	690	279.0	175.0	190.0	190.0	0	A	B3	19.5	14
57413	74	400	450	690	279.0	175.0	190.0	190.0	1	A	B3	19.5	14
57512	75	300	350	540	307.0	173.0	204.0	225.0	0	A	B7	19.5	2
57513	75	300	350	540	307.0	173.0	204.0	225.0	1	A	B7	19.5	2
57539	75	340	390	650	279.0	175.0	175.0	175.0	0	A	B3	17.2	14
57540	75	350	400	680	279.0	175.0	190.0	190.0	0	A	B3	19.5	14
58513	85	360	410	700	307.0	173.0	204.0	225.0	0	A	B7	20.9	2

-	40B19R	28	35	300	187	127	203	227	1	A, B	9.8	1	
-	40B19L	28	35	300	187	127	203	227	0	A, B	9.8	1	
-	42B19R	30	38	340	187	127	203	227	1	A, B	10.1	1	
-	42B19L	30	38	340	187	127	203	227	0	A, B	10.1	1	
NS40Z	36B20R	28	35	274	197	129	203	227	1	A, B	10.2	1	NS40Z(S)MF
NS40ZL	36B20L	28	35	274	197	129	203	227	0	A, B	10.2	1	NS40ZL(S)MF
NT60-S4	38B20R	28	35	332	197	129	203	227	1	A, B	10.2	1	
NT60-S4L	38B20L	28	35	332	197	129	203	227	0	A, B	10.2	1	
-	42B20R	30	38	340	197	129	203	227	1	A, B	10.6	1	
-	42B20L	30	38	340	197	129	203	227	0	A, B	10.6	1	
NS60	46B24R	36	45	325	238	129	203	227	1	A, B	12.4	1	NS60(S)MF
NS60L	46B24L	36	45	325	238	129	203	227	0	A, B	12.4	1	NS60(S)LMF
NT80-S6	50B24R	36	45	390	238	129	203	227	1	A, B	12.6	1	
NT80-S6L	50B24L	36	45	390	238	129	203	227	0	A, B	12.6	1	
NX100-S6	55B24R	36	45	433	238	129	203	227	1	A, B	12.6	1	
NX100-S6L	55B24L	36	45	433	238	129	203	227	0	A, B	12.6	1	
	60B24L	38	47	460	238	129	203	227	1	A, B	12.8	1	
	60B24R	38	47	460	238	129	203	227	0	A, B	12.8	1	
-	50D20R	40	50	350	208	173	185	207	1	A	12.6	2	A50D20RMF
		36	45	410	208	173	185	207	1	A	12.6	2	26-50SJK
		40	50	500	208	173	185	207	1	A	13.3	2	26-60
		40	50	410	208	173	202	225	1	A	13.6	2	50D20RMF
-	50D20L	40	50	350	208	173	185	207	0	A	12.6	2	A50D20LMF
		36	45	410	208	173	185	207	0	A	12.6	2	26R50SJK
		40	50	500	208	173	185	207	0	A	13.3	2	26R60SK
		40	50	410	208	173	202	225	0	A	13.6	2	50D20LMF
-	55D23R	44	55	430	231	173	186	208	1	A	14.4	2	
		44	55	525	231	173	186	208	1	A	14.9	2	
		44	55	550	231	173	186	208	1	A	15.2	2	85BR60K
		44	55	550	231	173	204	225	1	A	16.1	2	
-	55D23L	44	55	430	231	173	186	208	0	A	14.4	2	
		44	55	525	231	173	186	208	0	A	14.9	2	
		44	55	550	231	173	186	208	0	A	15.2	2	85B60K

		44	55	550	231	173	204	225	0	A	16.1	2	
-	65D23R	44	55	525	231	173	186	208	1	A	14.9	2	
		44	55	550	231	173	186	208	1	A	15.2	2	85BR60K
		44	55	550	231	173	204	225	1	A	16.1	2	
		52	65	490	231	173	204	225	1	A	16.1	2	25-60
-	65D23L	44	55	525	231	173	186	208	0	A	14.9	2	
		44	55	550	231	173	186	208	0	A	15.2	2	85B60K
		44	55	550	231	173	204	225	0	A	16.1	2	
		52	65	490	231	173	204	225	0	A	16.1	2	35-60
-	70D23R	44	55	525	231	173	186	208	1	A	14.9	2	
		44	55	550	231	173	186	208	1	A	15.2	2	85BR60K
		44	55	550	231	173	204	225	1	A	16.1	2	
		52	65	490	231	173	204	225	1	A	16.1	2	25-60
-	70D23L	44	55	525	231	173	186	208	0	A	14.9	2	
		44	55	550	231	173	186	208	0	A	15.2	2	85B60K
		44	55	550	231	173	204	225	0	A	16.1	2	
		52	65	490	231	173	204	225	0	A	16.1	2	35-60
-	75D23R	44	55	550	231	173	186	208	1	A	15.2	2	85BR60K
		44	55	550	231	173	204	225	1	A	16.1	2	
		52	65	520	231	173	204	225	1	A	16.1	2	
-	75D23L	44	55	550	231	173	186	208	0	A	15.2	2	85B60K
		44	55	550	231	173	204	225	0	A	16.1	2	
		52	65	520	231	173	204	225	0	A	16.1	2	
-	80D23L	54	68	580	231	173	204	225	0	A	16.6	2	
-	80D23R	54	68	580	231	173	204	225	1	A	16.6	2	
N50	48D26R	40	50	350	260	173	204	225	1	A	15.3	2	N50MF
N50L	48D26L	40	50	350	260	173	204	225	0	A	15.3	2	N50LMF
N50Z	55D26R	48	60	450	260	173	204	225	1	A	16.0	2	N50ZMF
N50ZL	55D26L	48	60	450	260	173	204	225	0	A	16.0	2	N50ZLMF
NS70	65D26R	52	65	550	260	173	204	225	1	A	17.7	2	
NS70L	65D26L	52	65	550	260	173	204	225	0	A	17.7	2	
-	75D26R	52	65	550	260	173	204	225	1	A	18.4	2	
-	75D26L	52	65	550	260	173	204	225	0	A	18.4	2	

NX110-5	80D26R	55	65	600	260	173	204	225	1	A	19.0	2	
NX110-5L	80D26L	55	65	600	260	173	204	225	0	A	19.0	2	
-	90D26R	58	68	680	260	173	204	225	1	A	19.6	2	
-	90D26L	58	68	680	260	173	204	225	0	A	19.6	2	
N70	65D31R	56	70	530	306	173	204	225	1	A	19.5	2	
N70L	65D31L	56	70	530	306	173	204	225	0	A	19.5	2	
N70Z	75D31R	60	75	630	306	173	204	225	1	A	19.9	2	
N70ZL	75D31L	60	75	630	306	173	204	225	0	A	19.9	2	
NX120-7	95D31R	64	80	650	306	173	204	225	1	A	20.9	2	
NX120-7L	95D31L	64	80	650	306	173	204	225	0	A	20.9	2	
-	105D31R	64	80	710	306	173	204	225	1	A	22.0	2	
-	105D31L	64	80	710	306	173	204	225	0	A	22.0	2	
N100(L)	95E41R(L)	80	100	625	332	174	220	240	3	A	25.9	6,7	1151/1151K
N100	95E41R	80	100	700	408	174	213	234	1	A	28.3	4	
N100L	95E41L	80	100	700	408	174	213	234	0	A	28.3	4	
N100Z	105E41R	83	100	750	408	174	213	234	1	A	28.3	4	
N100ZL	105E41L	83	100	750	408	174	213	234	0	A	28.3	4	
NS120	115E41R	88	100	760	408	174	213	234	1	A	29.2	4	
NS120L	115E41L	88	100	760	408	174	213	234	0	A	29.2	4	
-	120E41R	88	100	780	408	174	213	234	1	A	29.2	4	
-	120E41L	88	100	780	408	174	213	234	0	A	29.2	4	
NX200-10	130E41R	92	110	800	408	174	213	234	1	A	29.2	4	
NX200-10L	130E41L	92	110	800	408	174	213	234	0	A	29.2	4	
N120	115F51	96	120	750	505	182	213	234	4, 5	A	35.4	5	
-	130F51	96	120	800	505	182	213	234	4, 5	A	35.4	5	
NS150	145F51	112	135	850	505	182	213	234	4, 5	A	39.2	5	
NT200-12	150F51	108	135	916	505	182	213	234	4, 5	A	39.2	5	
-	160F51	112	135	1005	505	182	213	234	4, 5	A	39.2	5	
N150	145G51	120	150	930	508	215	213	234	4, 5	A	41.3	5	
-	160G51	120	150	950	508	215	213	234	4, 5	A	41.3	5	
NS200	165G51	136	-	933	508	215	213	234	4, 5	A	42.6	5	
NT250-15	180G51	128	160	1090	508	215	213	234	4, 5	A	42.6	5	
N200	190H52	160	200	924	512	277	220	241	4, 5	A	58.6	5	

-	210H52	160	200	1000	512	277	220	241	4, 5	A	58.6	5	
-	225H52	176	220	1313	512	277	220	241	4, 5	A	59.9	5	

FOR AMERICAN VEHICLES(BCI)

A. Passenger Car & Commercial Batteries 12 Volt(6 Cells)

BCI Group	Catalog No.	Cranking Amp. at 0 F (Amps.)	Reserve Capacity at 80 F (Min.)	Max. Overall Dimensions(mm)			LABEL SIZE			BCI Figure No.	Delkor Figure No.	Terminal Type	Weight with Acid (Kgs)
				Length	Width	T. Height	CAUTION	FRONT	SIDE				
21	21-410	410	80	208	173	222	170*98	140*70	-	10	2	A	13.3
21R	21R-410	410	80	208	173	222	"	"	-	11	2	A	13.3
22NF	22NF-330	330	60	240	135	205				11F	3	A	11.2
22F	22F-420	420	85	241	173	208	180*98	"	-	11F	3	A	14.2
	22F-450	450	90	241	173	208	"	"	-	11F	3	A	14.8
	22F-520	520	95	241	173	208	"	"	-	11F	3	A	15.3
	22F-550	550	90	241	173	208	"	"	-	11F	3	A	15.0
	22F-610	610	90	241	173	208	"	"	-	11F	3	A	15.2
	22F-630	630	90	241	173	208	"	"	-	11F	3	A	15.6
24	24-350	350	81	260	173	225	"	"	-	10	2	A	15.3
	24-450	450	90	260	173	225	"	"	-	10	2	A	16.0
	24-525	525	95	260	173	225	"	"	-	10	2	A	16.9
	24-550	550	110	260	173	225	"	"	-	10	2	A	17.7
	24-600	600	125	260	173	225	"	"	-	10	2	A	18.4
	24-630	630	130	260	173	225	"	"	-	10	2	A	19.0
	24-680	680	130	260	173	225	180*98	"	-	10	2	A	19.6
24-750	750	130	260	173	225	180*98	"	-	10	2	A	19.6	
24R	24R-350	350	81	260	173	225	"	"	-	11	2	A	15.3
	24R-450	450	90	260	173	225	"	"	-	11	2	A	16.0
	24R-525	525	95	260	173	225	"	"	-	11	2	A	16.9
	24R-550	550	110	260	173	225	"	"	-	11	2	A	17.7
	24R-600	600	125	260	173	225	"	"	-	11	2	A	18.4
	24R-630	630	130	260	173	225	"	"	-	11	2	A	19.0

	24R-680	680	130	260	173	225	180*98	"	-	11	2	A	19.6
	24R-750	750	130	260	173	225	180*98	"	-	11	2	A	19.6
24F	24F-350	350	81	272	173	225	"	"	-	11F	3	A	15.3
	24F-450	450	90	272	173	225	"	"	-	11F	3	A	16.0
	24F-480	480	101	272	173	225	"	"	-	11F	3	A	16.9
	24F-525	525	95	272	173	225	"	"	-	11F	3	A	16.9
	24F-550	550	110	272	173	225	"	"	-	11F	3	A	17.7
	24F-550	550	120	272	173	225	"	"	-	11F	3	A	18.7
	24F-600	600	125	272	173	225	"	"	-	11F	3	A	18.4
	24F-630	630	130	272	173	225	"	"	-	11F	3	A	19.0
	24F-680	680	130	272	173	225	"	"	-	11F	3	A	19.6
	24F-750	750	130	272	173	225	180*98	"	-	11F	3	A	19.6
25	25-520	520	112	230	173	225	"	"	-	10	2	A	16.1
	25-550	550	90	230	173	225	"	"	-	10	2	A	16.1
	25-580	580	110	230	173	225	"	"	-	10	2	A	16.7
26	26-350	350	78	208	173	205	170*98	"	-	10	2	A	12.6
	26-410	410	75	208	173	205	"	"	-	10	2	A	12.6
	26-500	500	80	208	173	205	"	"	-	10	2	A	13.3
26R	26R-350	350	78	208	173	205	"	"	-	11	2	A	12.6
	26R-410	410	75	208	173	205	"	"	-	11	2	A	12.6
	26R-500	500	80	208	173	205	"	"	-	11	2	A	13.3
27	27-530	530	120	306	173	225	180*98	"	-	10	2	A	19.5
	27-630	630	130	306	173	225	"	"	-	10	2	A	19.9
	27-650	650	150	306	173	225	"	"	-	10	2	A	20.9
	27-680	680	160	306	173	225	"	"	-	10	2	A	21.6
	27-710	710	160	306	173	225	180*98	"	-	10	2	A	22.0
27R	27R-530	530	120	306	173	225	180*98	"	-	11	2	A	19.5
	27R-630	630	130	306	173	225	"	"	-	11	2	A	19.9
	27R-650	650	150	306	173	225	"	"	-	11	2	A	20.9
	27R-680	680	160	306	173	225	"	"	-	11	2	A	21.6
	27R-710	710	160	306	173	225	180*98	"	-	11	2	A	22.0
27F	27F-530	530	120	318	173	225	"	"	-	11F	3	A	19.5
	27F-630	630	130	318	173	225	"	"	-	11F	3	A	19.9

	27F-650	650	150	318	173	225	"	"	-	11F	3	A	20.9
	27F-680	680	160	318	173	225	"	"	-	11F	3	A	21.6
	27F-710	710	160	318	173	225	"	"	-	11F	3	A	22.0
34	34-550	550	115	260	173	205	"	"	-	10	18	A	17.1
	34-610	610	110	260	173	205	"	"	-	10	18	A	17.2
34R	34R-550	550	115	260	173	205	"	"	-	11	18	A	17.1
	34R-610	610	110	260	173	205	"	"	-	11	18	A	17.2
35	35-520	520	112	230	173	225	"	"	-	11	2	A	16.1
	35-550	550	90	230	173	225	"	"	-	11	2	A	16.1
	35-580	580	110	230	173	225	"	"	-	11	2	A	16.7
41	41-550	540	110	279	175	175	"	"	-	15	12	A	16.4
	41-630	630	120	279	175	175	"	"	-	15	12	A	17.3
	41-650	650	100	279	175	175	"	"	-	15	12	A	17.3
42	42-410	410	75	243	175	175	197*77	140*70	-	15	12	A	13.4
	42-500	500	90	243	175	175	"	"	-	15	12	A	14.5
42R	42R-410	410	75	243	175	175	"	"	-	-	12	A	13.4
	42R-500	500	90	243	175	175	"	"	-	-	12	A	14.5
47	47-525	525	90	244	175	190	"	"	-	24	10	A	15.3
	47-580	580	95	244	175	190	"	"	-	24	10	A	15.9
48	48-500	500	110	279	175	190	106*67	170*60	-	24	14	A	17.3
	48-600	600	120	279	175	190	(2PIECE)	"	-	24	14	A	18.2
	48-680	680	135	279	175	190		"	-	24	14	A	19.5
49	49-650	650	170	354	175	190	45*67(2PIECE)	"	-	24	14	A	23.7
51	51-350	350	75	238	129	227	156*63	140*70	-	10	1	A	12.4
	51-405	405	75	238	129	227	"	"	-	10	1	A	12.6
	51-430	430	80	238	129	227	"	"	-	10	1	A	12.6
	51-460	460	85	238	129	227	"	"	-	10	1	A	12.8
51R	51R-350	350	75	238	129	227	"	"	-	11	1	A	12.4
	51R-405	405	75	238	129	227	"	"	-	11	1	A	12.6
	51R-430	430	80	238	129	227	"	"	-	11	1	A	12.6
	51R-460	460	85	238	129	227	"	"	-	11	1	A	12.8
58	58-460	460	70	243	185	177				26	27	A	12.3
	58-520	520	80	243	185	177				26	27	A	13.1

	58-560	560	80	243	185	177				26	27	A	13.8
	58-610	610	90	243	185	177				26	27	A	14.1
58R	58R-460	460	70	243	185	177				19	27	A	12.3
	58R-520	520	80	243	185	177				19	27	A	13.1
	58R-560	560	80	243	185	177				19	27	A	13.8
	58R-610	610	90	243	185	177				19	27	A	14.1
65	65-700	700	140	304	191	192				21	28	A	20.2
	65-850	850	160	304	191	192				21	28	A	21.0
70	70-350	350	78	208/217	179	186				17	23,24	G	12.4
	70-430	430	78	208/217	179	186				17	23,24	G	12.4
	70-525	525	80	208/217	179	186				17	23,24	G	13.2
70DT	70DT-350	350	78	208/217	179	186				-	25,26	A+G	12.6
	70DT-430	430	78	208/217	179	186				-	25,26	A+G	13.3
	70DT-525	525	80	208/217	179	186				-	25,26	A+G	13.7
74	74-350	350	81	260/269	180	206	180*98	"	-	17	23,24	G	15.4
	74-450	450	90	260/269	180	206	"	"	-	17	23,24	G	16.2
	74-525	525	95	260/269	180	206	"	"	-	17	23,24	G	17.1
	74-600	600	125	260/269	180	206	"	"	-	17	23,24	G	18.4
	74-680	680	130	260/269	180	206	"	"	-	17	23,24	G	19.7
75	75-430	430	90	230/239	179	186	"	"	-	17	23,24	G	14.4
	75-450	450	90	230/239	179	186	"	"	-	17	23,24	G	14.9
	75-500	500	90	230/239	179	186	"	"	-	17	23,24	G	14.9
	75-550	550	90	230/239	179	186	"	"	-	17	23,24	G	15.2
	75-610	610	90	230/239	179	186	"	"	-	17	23,24	G	15.2
	75-630	630	90	230/239	179	186	"	"	-	17	23,24	G	15.6
	75-650	650	90	230/239	179	186	"	"	-	17	23,24	G	16.0
75DT	75DT-430	430	90	230/239	179	186	"	"	-	-	25,26	A+G	14.4
	75DT-450	450	90	230/239	179	186	"	"	-	-	25,26	A+G	14.9
	75DT-500	500	90	230/239	179	186	"	"	-	-	25,26	A+G	14.9
	75DT-550	550	90	230/239	179	186	"	"	-	-	25,26	A+G	15.2
	75DT-610	610	90	230/239	179	186	"	"	-	-	25,26	A+G	15.2
	75DT-630	630	90	230/239	179	186	"	"	-	-	25,26	A+G	15.6
	75DT-650	650	90	230/239	179	186	"	"	-	-	25,26	A+G	16.0

78	78-520	520	100	260/269	179	186				17	23,24	G	16.2
	78-630	630	100	260/269	179	186				17	23,24	G	17.6
	78-670	670	110	260/269	179	186				17	23,24	G	17.6
	78-730	730	125	260/269	179	186				17	23,24	G	18.8
	78-790	790	115	260/269	179	186				17	23,24	G	18.7
78DT	78DT-520	520	100	260/269	179	205				-	25,26	A+G	16.5
	78DT-630	630	100	260/269	179	205				-	25,26	A+G	17.9
	78DT-670	670	110	260/269	179	205				-	25,26	A+G	18.0
	78DT-730	730	125	260/269	179	205				-	25,26	A+G	19.1
	78DT-790	790	115	260/269	179	205				-	25,26	A+G	19.0
85	85-430	430	90	230	173	205	"	"	-	11	2	A	14.4
	85-450	450	90	230	173	205	"	"	-	11	2	A	14.8
	85-525	525	90	230	173	205	"	"	-	11	2	A	14.9
	85-550	550	90	230	173	205	"	"	-	11	2	A	15.2
	85-610	610	90	230	173	205	180*98	"	-	11	2	A	15.7
	85-630	630	90	230	173	205	"	"	-	11	2	A	15.6
86	86-430	430	90	230	173	205	"	"	-	10	2	A	14.4
	86-450	450	90	230	173	205	"	"	-	10	2	A	14.8
	86-525	525	90	230	173	205	"	"	-	10	2	A	14.9
	86-550	550	90	230	173	205	"	"	-	10	2	A	15.2
	86-610	610	90	230	173	205	180*98	"	-	10	2	A	15.7
	86-630	630	90	230	173	205	"	"	-	10	2	A	15.6
90	90-410	410	75	243	175	175	197*77	"	-	24	10	A	13.4
	90-500	500	90	243	175	175	"	"	-	24	10	A	14.5
90R	90R-410	410	75	243	175	175	"	"	-	-	10	A	13.4
	90R-500	500	90	243	175	175	"	"	-	-	10	A	14.5
91	91-500	500	95	279	175	175	230*77	170*60	-	24	14	A	15.5
	91-550	550	110	279	175	175	"	"	-	24	14	A	16.4
	91-630	630	120	279	175	175	"	"	-	24	14	A	17.3
	91-650	650	100	279	175	175	"	"	-	24	14	A	17.3
93	93-750	750	165	354	175	175	45*67(2PIECE	"	-	24	14	A	22.8

B. Heavy-Duty Commercial Batteries 12 Volt(6 Cells)

BCI Group Size	Catalog No.	Cranking Amp. at 0 F (Amps.)	Reserve Capacity at 80 F (Min.)	Max. Overall Dimensions(mm)			LABEL SIZE			BCI Figure No.	Delkor Figure No.	Termin al Type	Weight with Acid (Kgs)
				Length	Width	T. Height	CAUTION	FRONT	SIDE				
4D	4D-950	950	300	508	215	234	230*130	230*80	95*75	8	5	A	41.3
	4D-1050	1050	320	508	215	234	"	"	"	8	5	A	42.6
8D	8D-1000	1000	430	512	277	241	"	"	"	8	5	A	58.6
	8D-1300	1300	440	512	277	241	"	"	"	8	5	A	59.9
31	31-550	550	130	330	173	239	180*120	-	-	18	6,7	A	23.4
	31-625	625	160	330	173	239	"	-	-	18	6,7	A	25.0
	31-625	625	180	330	173	239	"	-	-	18	6,7	A	25.9
	31-710	710	180	330	173	239	"	-	-	18	6,7	A	26.3
	31-750	750	160	330	173	239	"	-	-	18	6,7	A	24.7
	31-900	900	160	330	173	239	"	-	-	18	6,7	A	25.5
31T	31-550T	550	130	330	173	239	"	-	-	18	6,7	F	23.3
	31-625T	625	180	330	173	239	"	-	-	18	6,7	F	25.8
	31-750T	750	160	330	173	239	"	-	-	18	6,7	F	24.7
	31-900T	900	160	330	173	239	"	-	-	18	6,7	F	25.4
	31-580TE	580	180	330	173	239	"	-	-	18	6,7	F	26.0

C. General Utility Batteries 12 Volt(6 Cells)

BCI Group Size	Catalog No.	Cranking Amp. at 0 F (Amps.)	Reserve Capacity at 80 F (Min.)	Max. Overall Dimensions(mm)			LABEL SIZE			BCI Figure No.	Delkor Figure No.	Termin al Type	Weight with Acid (Kgs)
				Length	Width	T. Height							
U1	U1-230	230	21	197	130	186	156*63			10X	20	C	7.1
	U1-260	260	33	197	130	186	"			10X	20	C	7.8
U1R	U1R-230	230	21	197	130	186	"			11X	20	C	7.1
	U1R-260	260	33	197	130	186	"			11X	20	C	7.8

D. Marine / RV Batteries 12 Volt(6 Cells)

BCI Group	Catalog No.	Amps For Load Test	RC (Min)	Max. Overall Dimensions(mm)						Cold Cranking S.A.E. Spec J537H	Cranking Amps	Terminal Type	
				Length	Width	Hight	T. Height		Total Height				
24	M24	250	115	275	172	203	186	156*63		229	500	20(MCA)	SAE Posts / Wing Nut
27	M27	285	145	320	172	203	186	156*63		229	570	20(MCA)	SAE Posts / Wing Nut
31	M31	310	180	330	172	208	186	156*63		234	625	20(MCA)	SAE Posts / Wing Nut

Notes)

1. H : High Capacity battery
2. T : Stud type terminal battery
3. TE : Stud type terminal & Stationary power battery

FOR AUSTRALIAN VEHICLES

Model	Cranking Amp. at 18°C (Amps.)	Reserve Capacity at 25°C (Min.)	Max. Overall Dimensions(mm)			Cell Layout	Terminal Type	LABEL			MODEL	Weight with Acid (Kgs)	Delkor Figure No.
			Length	Width	T. Height			CAUTION	FRONT	SIDE			
U1-230	230	21	197	130	186	1	C	156*63	140*70	-	U1	7.1	20
U1-260	260	33	197	130	186	1	C	"	"	-	"	7.8	20
U1R-230	230	21	197	130	186	0	C	"	"	-	"	7.1	20
U1R-260	260	33	197	130	186	0	C	"	"	-	"	7.8	20
NS40Z	274	52	197	129	227	1	A, B	"	"	-	B20	10.2	1
NS40ZL	274	52	197	129	227	0	A, B	"	"	-	"	10.2	1
NS40ZZ	332	52	197	129	227	1	A, B	"	"	-	"	10.3	1
NS40ZZL	332	58	197	129	227	0	A, B	"	"	-	"	10.6	1
51-350	350	75	238	129	227	1	A, B	"	"	-	B24	12.4	1
51-405	405	75	238	129	227	1	A, B	"	"	-	"	12.6	1

51-430	430	80	238	129	227	1	A, B	"	"	-	"	12.6	1
51-460	460	85	238	129	227	1	A, B	-	10	1	A	12.8	1
51R-350	350	75	238	129	227	0	A, B	"	"	-	"	12.4	1
51R-405	405	75	238	129	227	0	A, B	"	"	-	"	12.6	1
51R-430	430	80	238	129	227	0	A, B	"	"	-	"	12.6	1
51R-460	460	85	238	129	227	0	A, B	-	10	1	A	12.8	1
2HN	405	75	258	135	227	0	A	180*66	"	-	NS10"	13.0	9
21-410	410	80	208	173	222	1	A	170*98	"	-	GP21	13.3	2
21R-410	410	80	208	173	222	0	A	"	"	-	"	13.3	2
58-460	460	70	243	185	177	1	A					12.3	27
58-520	520	80	243	185	177	1	A					13.1	27
58-560	560	80	243	185	177	1	A					13.8	27
58-610	610	90	243	185	177	1	A					14.1	27
58R-460	460	70	243	185	177	0	A					12.3	27
58R-520	520	80	243	185	177	0	A					13.1	27
58R-560	560	80	243	185	177	0	A					13.8	27
58R-610	610	90	243	185	177	0	A					14.1	27
85-430	430	90	230	173	205	0	A	180*98	"	-	GP85	14.4	2
85-450	450	90	230	173	205	0	A	"	"	-	"	14.8	2
85-525	525	90	230	173	205	0	A	"	"	-	"	14.9	2
85-550	550	90	230	173	205	0	A	"	"	-	"	15.2	2
85-610	610	90	230	173	205	0	A	"	"	-	"	15.7	2
85-630	630	90	230	173	205	0	A	"	"	-	"	15.6	2
86-430	430	90	230	173	205	1	A	"	"	-	"	14.4	2
86-450	450	90	230	173	205	1	A	"	"	-	"	14.8	2
86-525	525	90	230	173	205	1	A	"	"	-	"	14.9	2
86-550	550	90	230	173	205	1	A	"	"	-	"	15.2	2
86-610	610	90	230	173	205	1	A	"	"	-	"	15.7	2
86-630	630	90	230	173	205	1	A	"	"	-	"	15.6	2
25-520	520	112	230	173	225	1	A	"	"	-	GP25	16.1	2
25-550	550	90	230	173	225	1	A	"	"	-	"	16.1	2
25-580	580	110	230	173	225	1	A	-	10	2	A	16.7	2
35-520	520	112	230	173	225	0	A	"	"	-	"	16.1	2

35-550	550	90	230	173	225	0	A	"	"	-	"	16.1	2
35-580	580	110	230	173	225	0	A	-	10	2	A	16.7	2
22NF-330	330	60	240	135	205	1	A				22NF	11.2	3
22NF-330D	330	60	240	135	205	3	H				22NF	11.3	21
22F-420	420	85	241	173	208	0	A	"	"	-	22F	14.2	3
22F-450	450	90	241	173	208	0	A	"	"	-	"	14.8	3
22F-520	520	95	241	173	208	0	A	"	"	-	"	15.3	3
22F-550	550	90	241	173	208	0	A	"	"	-	"	15.0	3
22F-610	610	90	241	173	208	0	A	"	"	-	"	15.2	3
22F-630	630	90	241	173	208	0	A	"	"	-	"	15.6	3
22FR-420	420	85	241	173	208	1	A	"	"	-	"	14.2	3
22FR-450	450	90	241	173	208	1	A	"	"	-	"	14.8	3
22FR-520	520	95	241	173	208	1	A	"	"	-	"	15.3	3
22FR-550	550	90	241	173	208	1	A	"	"	-	"	15.0	3
22FR-610	610	90	241	173	208	1	A	"	"	-	"	15.2	3
22FR-630	630	90	241	173	208	1	A	"	"	-	"	15.6	3
22F-420D	420	85	241	173	212	3	H	180*65	"	-	"	14.4	21,22
22F-450D	450	90	241	173	212	3	H	"	"	-	"	15.0	21,22
22F-520D	520	95	241	173	212	3	H	"	"	-	"	15.5	21,22
22F-550D	550	90	241	173	212	3	H	"	"	-	"	15.2	21,22
22F-610D	610	90	241	173	212	3	H	"	"	-	"	15.4	21,22
22F-630D	630	90	241	173	212	3	H	"	"	-	"	15.8	21,22
90-410	410	75	244	175	175	0	A	197*77	"	-	DINL9"	13.4	10
90-500	500	90	244	175	175	0	A	"	"	-	"	14.5	10
47-525	525	90	244	175	190	0	A	"	"	-	DIN9"	15.3	10
47-580	580	95	244	175	190	0	A	"	"	-	DIN9"	15.9	10
24-350	350	81	260	173	225	1	A	180*98	"	-	GP24	15.3	2
24-450	450	90	260	173	225	1	A	"	"	-	"	16.0	2
24-525	525	95	260	173	225	1	A	"	"	-	"	16.9	2
24-550	550	110	260	173	225	1	A	"	"	-	"	17.7	2
24-600	600	125	260	173	225	1	A	"	"	-	"	18.4	2
24-630	630	130	260	173	225	1	A	"	"	-	"	19.0	2
24-680	680	130	260	173	225	1	A	"	"	-	"	19.6	2

24-750	750	130	260	173	225	1	A	-	10	2	A	19.6	2
24R-350	350	81	260	173	225	0	A	"	"	-	"	15.3	2
24R-450	450	90	260	173	225	0	A	"	"	-	"	16.0	2
24R-525	525	95	260	173	225	0	A	"	"	-	"	16.9	2
24R-550	550	110	260	173	225	0	A	"	"	-	"	17.7	2
24R-600	600	125	260	173	225	0	A	"	"	-	"	18.4	2
24R-630	630	130	260	173	225	0	A	"	"	-	"	19.0	2
24R-680	680	130	260	173	225	0	A	180*98	"	-	"	19.6	2
24R-750	750	130	260	173	225	0	A	-	10	2	A	19.6	2
24F-350	350	81	272	173	225	0	A	"	"	-	24F	15.3	3
24F-450	450	90	272	173	225	0	A	"	"	-	"	16.0	3
24F-480	480	101	272	173	225	0	A	"	"	-	"	16.9	3
24F-525	525	95	272	173	225	0	A	"	"	-	"	16.9	3
24F-550	550	110	272	173	225	0	A	"	"	-	"	17.7	3
24F-550	550	120	272	173	225	0	A	"	"	-	"	18.7	3
24F-600	600	125	272	173	225	0	A	"	"	-	"	18.4	3
24F-630	630	130	272	173	225	0	A	"	"	-	"	19.0	3
24F-680	680	130	272	173	225	0	A	"	"	-	"	19.6	3
24F-750	750	130	260	173	225	0	A	-	10	2	A	19.6	3
27-530	530	120	306	173	225	1	A	"	"	-	GP27	19.5	2
27-630	630	130	306	173	225	1	A	"	"	-	"	19.9	2
27-650	650	150	306	173	225	1	A	"	"	-	"	20.9	2
27-680	680	160	306	173	225	1	A	"	"	-	"	21.6	2
27-710	710	135	306	173	225	1	A	180*98	"	-	"	22.0	2
27R-530	530	120	306	173	225	0	A	"	"	-	"	19.5	2
27R-630	630	130	306	173	225	0	A	"	"	-	"	19.9	2
27R-650	650	150	306	173	225	0	A	"	"	-	"	20.9	2
27R-680	680	160	306	173	225	0	A	"	"	-	"	21.6	2
27R-710	710	135	306	173	225	0	A	180*98	"	-	"	22.0	2
65-700	700	140	304	191	192	0	A					20.2	28
65-850	850	160	304	191	192	0	A					21.0	28
91-500	500	95	279	175	175	0	A	230*77	170*60	-	DINL11"	15.5	14
91-550	550	110	279	175	175	0	A	230*77	"	-	"	16.4	14

91-630	630	120	279	175	175	0	A	230*77	"	-	"	17.3	14
91-650	650	100	279	175	175	0	A	230*77	"	-	"	17.3	14
48-500	500	110	279	175	190	0	A	106*67(2)	"	-	DIN11"	17.3	14
48-600	600	120	279	175	190	0	A	106*67(2)	"	-	"	18.2	14
48-680	680	135	279	175	190	0	A	106*67(2)	"	-	"	19.5	14
31-550	550	130	330	173	239	3	A	"	-	-	"	23.4	6
31-625	625	180	330	173	239	3	A	"	-	-	"	25.9	6
31-710	710	180	330	173	239	3	A	"	-	-	"	26.3	6
31-750	750	160	330	173	239	3	A	"	-	-	"	24.7	6
31-900	900	160	330	173	239	3	A	"	-	-	"	25.5	6
31-550T	550	130	330	173	239	3	F	"	-	-	"	23.3	6
31-625T	625	180	330	173	239	3	F	"	-	-	"	25.8	6
31-750T	750	160	330	173	239	3	F	"	-	-	"	24.7	6
31-900T	900	160	330	173	239	3	F	"	-	-	"	25.4	6
31-580TE	580	180	330	173	239	3	F	"	-	-	"	26.0	6
93-750	750	165	354	175	175	0	A	145*67(2)	170*60	-	DINL15"	22.8	14
49-650	650	170	380	175	190	0	A	145*67(2)	"	-	DIN15"	23.7	14
N100	750	185	408	174	234	1	A	230*125	230*80	95*75	100B	28.3	4
N100L	750	185	408	174	234	0	A	"	"	"	"	28.3	4
N100Z	850	220	408	174	234	1	A	"	"	"	"	29.2	4
N100ZL	850	220	408	174	234	0	A	"	"	"	"	29.2	4
N120	800	230	505	182	234	4,5	A	230*130	"	"	N120	35.4	5
N120Z	950	250	505	182	234	4,5	A	"	"	"	"	39.2	5
4D-950	950	300	508	215	234	4,5	A	"	"	"	N150	41.3	5
4D-1050	1050	320	508	215	234	4,5	A	"	"	"	"	42.6	5
8D-1000	1000	430	512	277	241	4,5	A	"	"	"	N200	58.6	5
8D-1300	1300	440	512	277	241	4,5	A	"	"	"	"	59.9	5